

# Timber Glow

## Acrylic Timber Finish

# TIMBER GLOW™

### FEATURES

**Timber Glow** is a premium quality with 100% acrylic coating, specifically designed and formulated for interior and exterior application on all types of timber.

Drying to a tough, flexible finish, **Timber Glow** affords excellent durability, especially designed to withstand the harsh Australian environment. When correctly applied, **Timber Glow** will protect against UV and moisture for up to 5 years.

**Timber Glow** has a smooth low sheen, and is available in a wide range of fashionable, natural, timber colours.

### RECOMMENDED USES

**Timber Glow** is ideally suited for use both interior and exterior on the following:

- Timber
- Fibre sheeting
- Particle board
- Suitably primed metal

**Timber Glow** can be easily applied by brush, roller or airless spray. At least 2 coats are required for optimum performance and protection.

### SPECIFICATION DATA

<b>Generic Type:</b>	Water borne Acrylic	<b>Volume Solids:</b>	~37% <sup>(1)</sup>
<b>Finish:</b>	Low sheen	<b>Dry Film Thickness:</b>	30 – 40µ DFT
<b>Colour:</b>	Natural, <i>(Full Huecoat Timber Glow Colour Range)</i>	<b>Wet Film Thickness:</b>	80 - 110µ WFT
<b>Density:</b>	~1.38 g/cc <sup>(1)</sup>	<b>Coverage:</b>	10 - 12 m <sup>2</sup> / litre <sup>(1)</sup>
<b>Packaging:</b>	1,4 and 10 litre.	<b>Number of coats:</b>	2 coats Min
<b>Application:</b>	Brush, roller and airless spray	<b>Touch Dry:</b>	30 minutes
<b>Thinner:</b>	Water	<b>Dry to Recoat:</b>	2 hours
<b>Cleanup:</b>	Water	<b>Hard Dry:</b>	Overnight
		<b>Storage:</b>	Store under cool dry conditions
		<b>VOC Content:</b>	2.5-3.0%

<sup>(1)</sup>Based on Timbers, colours may vary.

## DIRECTIONS FOR USE

Ensure all surfaces are clean, dry, and free from oil, grease and dust. Make any necessary repairs prior to Sealing and Coating.

Chalky or powdery surfaces should be sanded to remove any loose material and Sealed.

Oiled timber should be thoroughly sanded and solvent cleaned with mineral turps followed by Timber Clean prior to application.

Unpainted new timber does require Timber Sealer. Then priming with Huecoat **Timber Seal** is recommended to prevent tannin staining, which may be visible on the surface (transported by the movement of water).

Stir well and ensure colour is as required before use. Provide adequate natural ventilation during use. Wash equipment immediately after use with water.

**DO NOT apply if temperature is below 10°C, or relative humidity is above 85%.  
DO NOT apply if moisture in timber is above 23% or less than 7%.**

### Typical Specifications

Surface	Preparation	System	Dry Film Build
previously painted surfaces	Surfaces should be sanded with all loose flaking paint removed. Ensure that surfaces are clean, dry and dust free.	1. Timber Glow 2. Timber Glow	30 - 40µ 30 - 40µ
Hard and Soft Woods , fibre sheeting and particle board	Surfaces should be thoroughly sanded. Ensure that surfaces are clean, dry and dust free.	1. Timber Seal 2. Timber Glow 3. Timber Glow	30 - 40µ 30 - 40µ 30 - 40µ
All North and West Elevations	Surfaces should have one coat Timber Seal and minimum Three Coats of Timber Glow	4. Timber Glow	30 - 40µ
Previously oiled timber	Surface should be thoroughly sanded and prepared as per SSPC-SP-1	1. Timber Seal 2. Timber Glow 3. Timber Glow	30 - 40µ 30 - 40µ 30 - 40µ
Steel or galvanised surfaces	Thoroughly scrub the surface to remove any white corrosion products and surface contamination (oil, grease etc). Prepare substrate to SSPC-SP-1.	1. Galvabond 2. Timber Glow 3. Timber Glow	25 - 30µ 30 - 40µ 30 - 40µ

## PRECAUTIONS

See the Huecoat Paints General Safety Data Sheet, Product label, and Material Safety Data Sheet (MSDS) for health and safety information prior to use.

## HUECOAT PAINTS

### Manufacturers of a complete range of quality paints

A Division of Acebound Noninees Pty Ltd ABN 74 247 708 978  
14 Fields Street, PINJARRA, Western Australia 6208  
PO Box 395, PINJARRA, Western Australia 6208  
Telephone (+61) 8 9409 9948  
[admin@huecoat.com](mailto:admin@huecoat.com)  
[www.huecoat.com](http://www.huecoat.com)

#### Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.